

Nedsänkbara pollare

Från trafikreglering till hög säkerhet

	Citeasy	Citeasy evo	Citeasy boost	Citeasy evo+	Citeasy evo800	Citydro boost	Citeco	Citadine	Protection	Sécurité
	Mekanisk	Mekanisk	Mekanisk	Manuell	Manuell	Hydraulisk	Elektrisk	Elektrisk	Elektrisk	Elektrisk
Kollisions- motstånd*	50 kJ	250 kJ	400 kJ	661 kJ	1223 kJ	400 kJ	250 kJ	661 kJ	1223 kJ	1860 kJ
Motsvarande kJ: Fordonsvikt Hastighet	 1,5 t - 30 km/h	 1,5 t - 66 km/h	 3,5 t - 55 km/h	 3,5 t - 70 km/h	 7,5 t - 65 km/h	 3,5 t - 55 km/h	 1,5 t - 66 km/h	 3,5 t - 55 km/h	 7,5 t - 65 km/h	 7,5 t - 80 km/h
Intrångs- resistens	150 kJ	750 kJ	1200 kJ	1983 kJ	3669 kJ	1200 kJ	750 kJ	1983 kJ	3669 kJ	5580 kJ
Pollarhöjd mm	600	600	600	600	800	600 (även 800)	600	600 (även 800)	800	1000
Pollardiameter mm	256	221	256	256	256	256	221	256	256	275
Godstjocklek mm	8	10	12,5	20	20	12,5	10	20	20	30
Fundament- storlek (B×L×D)	380×380×788	425×663×900	385×385×916	480×940×1050	480×940×1390	385×385×916	425×663×900	480×940×1050	480×940×1050	610×1160×2028
Rörelser/dag	10	10	10	10	10	1500	5000	6000	7000	7000
Drivgaranti	-	-	-	-	-	2 år	3 år	5 år	5 år	5 år
Konceptgaranti	2 år	2 år	2 år	2 år	2 år	2 år	Livstid	Livstid	Livstid	Livstid

*Kollisionsmotstånd för pollare = förblir funktionsduglig efter en stöt eller till och med flera upprepade stötar med denna kraft.